

PM8SIW

MOTOR	Permanent magnet DC motor
PROTECTION	Totally enclosed (IP54)
GEARBOX	In-line worm (SIW)
MOTOR POWER	13 - 48 Watts
SPEED	1 - 235 rpm
VOLTAGE	12V - 220V DC available range
WEIGHT	1.7 kg
RADIAL LOAD	78 N
AXIAL LOAD	49 N
SHAFT TYPE	Single ended shaft
EXTRAS	See page 36



See page 158 to specify shaft and gearbox position

Motor Power Cont. (W)		13	17	25	33	TORQUE (Nm)					
Motor Power 1 Hour (W)		15	21	33	40						
Motor Power 15 Min (W)		18	24	36	48						
Ratio INT	Ratio Final	MOTOR SPEED (rpm)				CONTINUOUS		1 HOUR		15 MINUTE	
		1500	2000	3000	4000	Composite	Bronze	Composite	Bronze	Composite	Bronze
		OUTPUT SPEED (rpm)									
54	25	1	1.5	2	3	7.0	11.3	7.0	11.3	7.0	11.3
27	25	2	3	4	6	7.0	11.3	7.0	11.3	7.0	11.3
14 1/2	25	4	6	8	11	7.0	9.3	7.0	11.3	7.0	11.3
8 1/3	25	7	10	14	19	6.2	6.2	7.0	8.2	7.0	8.9
16 1/2	8 1/3	11	15	22	29	4.7	4.7	6.2	6.2	6.7	6.7
12 1/2	8 1/3	14	19	29	38	3.8	3.8	5.1	5.1	5.5	5.5
10 1/3	8 1/3	17	23	35	46	3.3	3.3	4.4	4.4	4.8	4.8
9 1/3	8 1/3	19	26	39	51	3.1	3.1	4.1	4.1	4.5	4.5
8 1/3	8 1/3	22	29	43	58	2.8	2.8	3.8	3.8	4.1	4.1
7 1/4	8 1/3	25	33	50	66	2.6	2.6	3.4	3.4	3.7	3.7
6 1/4	8 1/3	29	38	58	77	2.3	2.3	3.0	3.0	3.3	3.3
5 1/6	8 1/3	35	46	70	93	2.0	2.0	2.6	2.6	2.8	2.8
6 1/4	6 1/4	38	51	77	102	1.8	1.8	2.4	2.4	2.7	2.7
5 1/6	6 1/4	46	62	93	124	1.6	1.6	2.1	2.1	2.3	2.3
5 1/6	5 1/6	56	75	112	150	1.4	1.4	1.8	1.8	2.0	2.0
4 1/8	5 1/6	70	94	141	188	1.2	1.2	1.5	1.5	1.7	1.7
4 1/8	4 1/8	88	118	176	235	1.0	1.0	1.3	1.3	1.4	1.4

in-line worm

